



**Project planning for the transformation of geographic
data from Irish Grid (IG) to Irish Transverse Mercator
(ITM)**

Information Paper

**Issued By:
Ordnance Survey Ireland (OSi)
Phoenix Park
Dublin 8
Ireland**

Date: June 2008

Table of contents:

1. Introduction	3
1.1 What is ITM.....	4
1.2 Why was ITM developed?.....	4
2. Benefits of Migrating to ITM	5
2.1 Compatibility with GPS	5
2.2 Improved Positional Accuracy.....	5
2.3 Use of the active GPS control network	5
2.4 Standardised co-ordinate system for Europe	5
2.5 Cheaper data capture	6
2.6 Compatibility with other ITM users	6
2.7 Better map indexing	6
3. Implications of moving to ITM	7
3.1 Software costs	7
3.2 Hardware costs	7
3.3 Migration project costs	7
3.4 Project management costs.....	7
4. General Migration Process.....	8
5. Migration Plan	9
5.1 Assessment of requirements.....	9
5.2 Migration project planning.....	10
5.3 Upgrade software to process ITM data	10
5.4 Test migration of samples of each type of data.....	11
5.5 Obtaining and loading ITM mapping	11
5.6 Migration of overlay data in chunks and checking.....	11
5.7 Solutions Providers	11
5.8 Migration of discrete datasets and checking	12
5.9 Migration of other geo-referenced datasets and checking	13
5.10 Check applications on new data	13
5.11 Modify user business processes	13
6. Sample Local Authority Case Study.....	14
6.1 Migrating different types of data.....	15
7. Quality checks.....	17
8. FAQ.....	18

1. Introduction

The purpose of this document is to assist users of Ordnance Survey Ireland (OSi) data to migrate from Irish Grid (IG) to Irish Transverse Mercator (ITM).

This document is the latest in a series of consultation and information papers issued by OSi and key stakeholders; notable dates in the lineage of ITM include:

- 1999 Concept introduced at ‘Survey Ireland 1999’ conference
- 2000 Preliminary user information circulated
- 2001 Consultation paper circulated
- 2001 ITM parameters formally adopted at ‘Survey Ireland 2001’
- 2002 OSi converts production flowlines to ITM
- 2002/3 ITM Technical Working Group
- 2002 ‘Grid InQuest’ transformation utility available
- 2002 On-line transformation utility available on OSi website
- 2004 Irish Institution of Surveyors (IIS) recommends ITM adoption
- 2005 Property Registration Authority goes digital with ITM

Key reference documents and papers include:

- 1999 - Making Maps Compatible with GPS
(see: <http://www.osi.ie/publications/geodetic.shtml>)
- 2000 - A New Co-ordinate System for Ireland - Preliminary User Information
(see <http://www.osi.ie/publications/papers.shtml>)
- 2001 - Co-ordinate Positioning Strategy - Information Paper
(see: <http://www.osi.ie/publications/geodetic.shtml>)
- 2001 - New Map Projections for Ireland - Consultation Paper
(see <http://www.osi.ie/publications/papers.shtml>)

1.1 What is ITM

ITM is a newly derived GPS compatible mapping projection that is associated with the ETRS89 and the GRS80 ellipsoid. It takes advantage of the accuracy of GPS whilst minimising mapping distortions. The true origin and central meridian defined in the Irish Grid is maintained, thus distributing the distortions due to the projection evenly.

Consideration was given to the introduction of a scale factor of unity on the central meridian. However, using a scale of 0.99982 results in two standard parallels, and the magnitude and effects of scale change are minimised.

The position of the false origin is moved to a point 600,000m west and 750,000m south of the true origin. This results in grid co-ordinates that are significantly different from IG, but does not introduce additional distortion or complexity. The magnitude of the shift ensures that IG co-ordinates plotted on the ITM projection do not fall on Ireland or Northern Ireland, and vice versa.

Technical Information		
Reference Ellipsoid:	GRS80	
Central Meridian:	8° West	
Scale on CM:	0.999 820	
True Origin:	Latitude (Φ)	53° 30' North
	Longitude (λ)	8° 00' West
False Origin (metres):		600 000 W
		750 000 S

1.2 Why was ITM developed?

- The extensive use of GPS in surveying
- The need for interoperability between GPS & geographic data
- International compatibility
- Shortcomings of the 'Irish Grid' which:
 - Is not GPS compatible
 - Is dependant on a transformation relationship to GPS
 - Contains legacy distortion issues
 - Can only be realised to IG to better than 1m using GPS

2. Benefits of Migrating to ITM

2.1 Compatibility with GPS

GPS and Irish Grid co-ordinates are based on different geodetic systems and are therefore not compatible. In order to overlay GPS data collected onto base-mapping in Irish Grid, the GPS co-ordinates need to be mathematically transformed to fit with the Irish Grid co-ordinates. This transformation results in a distortion of the GPS measurements. ITM is compatible with GPS data as both are based on a common geodetic datum (ETRF89), as a result, no transformation is needed to overlay GPS data on ITM mapping, therefore maintaining the accuracy of the GPS measurements.

2.2 Improved Positional Accuracy

One of the main benefits of the ITM map projection is the ability to obtain improved positional accuracy of data. This positional accuracy is achieved through;

- Use of a co-ordinate system that is compatible with GPS
- Use of new OS active control network for data capture
- The collection and re-alignment of base OS map data to these standards

2.3 Use of the active GPS control network

The GPS network provides an infrastructure of permanently recording active GPS reference stations as a continuous network throughout Ireland. If users are using the ITM co-ordinate system, which is compatible with GPS, they can post-process data collected from low cost single GPS receivers with data from the active GPS control network. This will provide significantly improved accuracy than what would be originally obtained from the GPS, an accuracy that would normally only be achievable using a more expensive GPS system.

2.4 Standardised co-ordinate system for Europe

Data in ITM projection is compatible with the standard co-ordinate system used across Europe (European Terrestrial Reference System – *ETRF89*). If standardisation with the European Union is specified in a particular project, then use of the ITM co-ordinate system will ensure compliance with such specifications.

2.5 Cheaper data capture

The benefits outlined above ultimately result in cheaper data capture for the user, the data can be input directly from the survey, no correction is needed which reduces processing time and costs. The data will also have an improved positional accuracy as a result of the use of ITM. The use of the active GPS control network allows the user to obtain accurate data using a much cheaper system.

2.6 Compatibility with other ITM users

Over time, it is expected that most users will migrate to ITM. Currently the Property Registration Authority (PRA) have 9 counties fully migrated to ITM projection. Table 1 shows the complete counties, those currently in Quality Assurance (QA) and those due to be completed next. By using the ITM map projection, users will have compatibility with other ITM users, such as the PRA, which will make data interchange easier and remove the introduction of errors as a result of data transformation.

Counties Live in PRA Digital Mapping Project (ITM)	Counties currently in QA Process
Carlow Clare Kilkenny Longford Louth Meath Wesmeath Wexford Wicklow	Dublin Roscommon
	Counties due to be digitised next
	Cavan Cork Kilkenny Sligo

Table 1: http://www.landregistry.ie/eng/Digital_Mapping_Project

27th January 2008

2.7 Better map indexing

ITM provides continuous mapping, which means that there are no sheet boundaries as with IG data. However, a map index has been created which uses a 1km grid, with each 1km tile referenced by the co-ordinate location of the bottom left corner of that tile. The main advantage this square-based grid has over the current arbitrary sheet index is that it allows for faster access to map tiles through a better geo-referenced index. If the current sheet index was to be maintained the sheet numbers would bear no reference to the ITM co-ordinates. If the current sheet tiles were to be maintained and the reference number changed to the ITM co-ordinates of the bottom left corner, the translation would result in uneven numbers with up to 3 places of decimal. To base a tile name on the combination of these numbers would result in an impractical 12+ digit name, hence the decision to create a new 1km gridded index specific to ITM co-ordinates.

3. Implications of moving to ITM

This section attempts to evaluate the implications of moving to ITM in terms of direct and indirect costs to the user, including the expected costs of project management.

3.1 Software costs

The migration process from IG to ITM may require an upgrade in standard software and in-house software/applications. The cost of this should be included within the software maintenance costs of the user business. The user may also need to purchase stand alone translation software or a translation service from a solutions provider. OSi have provided a free online co-ordinate converter at <http://www.osi.ie/gps/index.asp>. OSi have also produced a .dll file which has been made freely available to all major software providers to allow them to easily integrate the transformation polynomial in their software.

3.2 Hardware costs

It may be necessary to provide extra hardware for the extra data storage required during the data migration. This is likely to be required anyway as part of the continuing development programme, and can be planned for within the users hardware replacement programme.

3.3 Migration project costs

Once software to support ITM has been upgraded or installed, the cost of migrating from IG to ITM is reduced to process of migrating the users own data to ITM, and the project management of this process. This is considered to be the main cost of migration, and ultimately involves the cost of staff time to undertake the work. If this migration project is planned carefully and implemented thoroughly, the cost of this work on the user should be minimal.

3.4 Project management costs

Project management activities may include:

- Education in the requirements and implications of migration process
- Planning the process (obtaining timings for release of new data and software and estimating resources required for process (staff, time, hardware)
- Managing the migration process;
- Quality assessment of the migrated data

4. General Migration Process

In order to carry out a successful migration from IG to ITM, the following provides a simple 11-point plan:

1. Assess requirements
 - identify the datasets to be converted
2. Plan migration project
 - produce a detailed project plan
3. Upgrade software
 - to ensure that your software can process ITM
4. Upgrade GPS devices
 - to ensure that the GPS devices provide co-ordinates in ITM
 - to ensure that ITM mapping is supported
5. Test migration of samples of data
 - for each type of data
6. Obtain and load ITM mapping
 - ITM data is available from OSi
7. Migrate overlay data in chunks
 - check to ensure successful conversion
8. Migrate discrete datasets
 - check to ensure successful conversion
9. Migrate other geo-referenced datasets (if required)
 - check to ensure successful conversion
10. Check applications on new data
 - to ensure that they function
11. Modify business processes where incompatible with third parties
 - for example where input or output is in different coordinates

5. Migration Plan

5.1 Assessment of requirements

Different types of data require different processes for conversion. Before commencing the conversion process, it is therefore necessary to catalogue the data that is to be converted. This cataloguing should identify all the datasets, categorised as follows:

- Mapping
 - Copies of OSi data for traditional mapping use, held either as map tiles or as a continuous coverage.
- Mapping as background for user data
 - Overlays to OSi map base, held either as map tiles or as a continuous coverage, e.g. utility underground plant data.
- Additional discrete geo-referenced data
 - Aerial surveys, either a strip of images, or a continuous coverage over a defined area.
 - Engineering drawings, discrete geo-referenced plans.
 - Local plans, discrete geo-referenced drawings.
- Other geo-referenced datasets
 - Alphanumeric datasets that include coordinates (e.g. environmental observations).
- Data derived from map data
 - Datasets derived from using map features to create new objects, e.g. land ownership parcels.

For each category of data (vector, raster or aerial photography, continuous or discrete, maintained, historic, archived):

- what coordinate reference system is used (IG, ITM, ...)?
- how is the data related to OSi mapping (by coordinates, linked to cartographic features)?
- what is the positional accuracy requirement?
- what applications use the coordinates of the data?
- does the data need to be migrated?

5.2 Migration project planning

Planning is the key to the conversion process. A detailed plan needs to be drawn up. This should cover the stages identified here, with the detailed of how they will be carried out, by whom, when, and the resource requirements.

5.3 Upgrade software to process ITM data

Table 2 below outlines the current status of the main application providers. It will be necessary to confirm with your supplier whether they currently support ITM mapping and/or transformations, and if not, when they plan to implement this (if at all). It may be necessary to upgrade your software. Software applications which have been developed in-house will also need to be considered. Some data inputs and outputs may still require IG. Conversion between IG and ITM can be carried out in real-time for this (converters are available from OSI).

Current Status of Main Application Providers (*incomplete*)

ArcGIS	Current version of ArcGIS has a transformation but does not use OSi dll file or polynomial formula. Expect announcement for ESRI Ireland in June 2008.
Blue Marble	Provide co-ordinate conversion services – verification is on-going.
CadCorp	GIS software provider – has translation abilities – verification is on-going.
FME	Are in the process of implementing dll file - 1-2 months away from release.
MapInfo	GIS software provider - Projection algorithm included in 9.0 releases- – verification is on-going.
Microstation	Awaiting response.
GeoMedia	Will use FME transformation.

Table 2

5.4 Test migration of samples of each type of data

Before carrying out migration, the migration process should be tested on samples of each type of data identified in the assessment of requirements.

5.5 Obtaining and loading ITM mapping

Digital map data and paper maps are available from OSi in the normal way. Conversion is equivalent to receiving an update of the full set of map data. ITM data is continuous, and not based on map tiles like IG data.

5.6 Migration of overlay data in chunks and checking

Software for converting from IG to ITM may be provided either from your software supplier, or from OSi. For each type of data, the conversion process should be carried out in stages, for manageable “chunks” of data. This should include vector overlays, raster data and aerial photography. On completion of conversion, the data should be checked to ensure that it has been carried out successfully (completely and accurately).

5.7 Solutions Providers

The following companies can provide assistance in converting data from IG to ITM;

- **1Spatial**
1 Nore House,
Riverview Business Park,
Mahon,
Cork

Tel: +353 (0)21 4359595
Fax: +353 (0)21 4359596
E-mail: info@1spatial.com
- **Atlas Computers**
15 Moyville Lawns,
Taylors Lane. Rathfarham,
Dublin 16

Tel: +353 1 4958714
Fax: +353 1 4958717
E-mail: support@atlascomputers.ie

- **Compass Informatics**
19 Grattan Street
Dublin 2

Tel: +353-1-6612483
Fax: +353-1-661 2484
Web: www.compass.ie

- **ESBI Computing Ltd**
27 Lower Fitzwilliam Street
Dublin 2

Tel: +353-1-7026768 / 7027275
Fax: +353-1-6618455
Web: www.esbic.ie

- **Gamma**
4 Inns Court, Winetavern Street,
Dublin 8

Tel: +353-1-7079888
Fax: +353-1-6776787
Web: www.gamma.ie

- **IMGS**
8b Keypoint, Rosemount Business Park
Dublin 15

Tel: +353-1- 8853839
Fax: +353-1- 8853765
Web: www.imgs.ie

- **Mapflow**
4 Merrion Square,
Dublin 2

Tel: +353-1- 634 1430
Web: www.mapflow.ie

5.8 Migration of discrete datasets and checking

Separate datasets, such as inset drawings and detailed plans may not need to be converted, as they can be converted “on the fly” if required. However, if they are required to be converted, on completion of conversion, the data should be checked to ensure that it has been carried out successfully (completely and accurately).

5.9 Migration of other geo-referenced datasets and checking

Other datasets that do not appear to be map-based may nevertheless contain coordinates. Examples of this are environmental and other observational data. The occurrence of such coordinates needs to be identified, and they can be transformed by software. This may require help from your software supplier.

5.10 Check applications on new data

On completion of the conversion, all applications of the data need to be checked using test data, to ensure that they continue to work. This testing should be equivalent to the User Acceptance Testing (UAT) for the application.

5.11 Modify user business processes

Where data is passed to or from other organisations, conversion between IG and ITM may be required in the process to ensure compatibility of data.

6. Sample Local Authority Case Study

The local authority has:

- Two GIS for different applications
- A map library (all OSi vector, raster 6" & 50K, orthophotography)
- All mapping sheet based, not continuous
- Point locations of public buildings (including housing)
- Overlay polygons of planning applications
- Overlays of water & sewer networks
- Overlays of street furniture, highway maintenance, planned schemes
- Overlays of boundaries (high resolution)
- Project and scheme maps
- Historic archive of additional data (AutoCAD drawings)
- Input from contractors and consultants
- Supply data to National Roads Authority, Environmental Protection Agency, Planning Appeals Board

Each of these aspects needs to be included in the migration plan, each following the appropriate migration method.

6.1 Migrating different types of data

Migrating Mapping

OSi ITM digital map data is available from OSi in the normal way.

Migrating of non-OSi raster data and aerial photography

Raster images may only need to be transformed where they are used as a backdrop, e.g. orthophotos. They can be transformed using the IG to ITM transformation. However, the joins between the pixels will be rotated forming cracks (lack of join along the edges) of what would previously have been seamless image maps. It may be better to get this done by an external service.

Creating map indexes

IG data was stored in map tiles, ITM data is a continuous dataset (which may be cut to a prescribed area using relevant coordinates).

Since ITM data is continuous and not based on map tiles like IG data, the concept of map sheets is no longer relevant. However, many organisations use map sheets as a way of accessing and referring to mapping. If required, a map sheet index equivalent to that used for IG data can be provided, defining the extent (in ITM) of each map sheet. This could be used to maintain existing user processes, and while not essential, may be necessary in applications that are based on map tiles. If your current mapping is not continuous, now would be a good time to move to continuous mapping.

Metadata

Metadata, describing the user data and the state of data maintenance, which may be based upon IG map tiles will also need to be upgraded.

Migrating vector overlay data

Software for converting from IG to ITM should be provided by your software supplier. Most suppliers provide coordinate transformations, and the relevant transformation parameters are available on the OSi website. OSi provide conversion routines from IG to ITM. The migration process should be carried out in stages, for manageable “chunks” of data.

Migrating discrete geo-referenced data

Discrete datasets such as aerial surveys, either a strip of images or a continuous coverage over a defined area, engineering drawings, local plans, discrete geo-referenced plans and drawings, will not need to be migrated if they are not geo-referenced (i.e. contain inherent coordinates to position them, e.g. by corner points). Even if they are geo-referenced, they could be left as they are and converted “on the fly” if and when needed. However, if they are required to be converted, this should

not represent a problem to any geographic system. However the very size of raster images makes their manipulation much more problematic than for simple raster and attributed data. There are no geometrical or positional issues associated with this.

Migrating other geo-referenced datasets

Other datasets that do not appear to be map-based, may nevertheless contain coordinates. Examples of this are environmental and other observational data. The occurrence of such coordinates needs to be identified, and they can be transformed by software, if required. This may require help from your software supplier. In some cases coordinates can be left as they are and transformed on use.

Data derived from map data

If there are datasets derived from using map features to create new objects, e.g. land ownership parcels, two approaches are possible. One is to transform the coordinates as for other data containing coordinates. The other is to identify the features used to make up the object, and to take the corresponding feature from the ITM data.

7. Quality checks

A formal process of quality checks is required to ensure that all the data has been successfully migrated. The following criteria could be used:

- Completeness - Has all the data been converted?

To check this,

1. Check that all files (datasets, drawings) have been migrated.
2. For all major datasets, take a random selection of features (e.g. buildings), and check that they are in the migrated dataset.

- Relative positional accuracy - Are there any gross errors?

To check this,

1. For graphics files, compare visually for gross errors.
2. For continuous mapping, make a visual check for gross errors at any internal file boundaries (edge matching).

- Junction closing (overshoots/undershoots) - Are all junctions between links closed (nodes and polygons)

To check this, take a selection of areas (e.g. map tiles) and make a visual check that there are no unclosed junctions. If any are found, check that they whether or not they are in the original data.

- Raster overlays - Does transformed dataset fit correct extent?

To check this,

1. For a selection of files, check that they are in the correct place in space.
2. For continuous coverage's, check that there is continuity across the file boundaries. Note that there may be slight gaps or overlaps in raster data along the boundary of different files.

- Edge matching – are there any mismatches across boundaries of map sheets?

To check this, for continuous map background and overlays, carry out a visual check across sheet boundaries, for gross mismatches. If any are found, check that they whether or not they are in the original data.

- Use in applications - Do applications work with transformed data?

To check this, test each application (with test user data where appropriate) to ensure that it works. This test should be equivalent to the User Acceptance Test for the application.

8. FAQ

1. Do I need to migrate now?

It is not essential that you migrate now, but the longer that you delay, the more work you will have to do in the long run. It is important to plan now, to ensure that migration can be carried out with the minimum of effort, and to fit in with your other activities.

2. Will conversion to ITM cause a mismatch between my overlay data and the base mapping

This will depend on the quality of your data. Where overlays are recorded on up-to-date OSi mapping, there should not be a problem as the same linear transformation is used for both sets of data, but where historic mapping is used (for example county series) there could be a problem across sheet boundaries.

3. How do I know if my mapping and applications software can cope with ITM?

Page 10 of this document outlines the current status of some of the main software providers. After consulting this, confirm status with your system supplier, and then carry out tests.

4. Do we need to migrate all our data?

Not necessarily, once your data audit is complete you might decide to leave some data in IG, e.g. datasets that you keep for historical reference purposes only that were created in IG might be left in IG.

You could also elect to convert some data “on the fly” as you access it i.e. by using the convertor tools within your CAD / GIS software. However this decision means that you are now managing data within IG and ITM, and complications could result.

5. Will migration take a long time?

Not if it is planned properly. It should only be a few days, depending on data volumes. Project management and quality checking are essential, and will take more time.

6. Will migration cost a lot of money?

The migration process from IG to ITM may require an upgrade in standard software and in-house software/applications. The cost of this will most probably be included within your software maintenance agreement. Outside of this the main costs will be in staff time for project management and quality assurance.

7. How will migration of my data affect other organisations that I interchange data with?

Translators are available to transform input and output data between IG and ITM. Eventually, all systems will use ITM rather than IG.

8. Will migration lead to degradation in the quality of my data?

It should not have any significant effect. The decrease in positional accuracy due to transformation should be negligible, and more than offset by the improved positional accuracy of newly surveyed data.

9. Where do I find the IG (Irish Grid) to ITM translator?

<http://www.osi.ie/gps/index.asp>

10. Where so I get more information

1999 - Making Maps Compatible with GPS
(see: <http://www.osi.ie/publications/geodetic.shtml>)

2000 - A New Co-ordinate System for Ireland - Preliminary User Information
(see <http://www.osi.ie/publications/papers.shtml>)

2001 - Co-ordinate Positioning Strategy - Information Paper
(see: <http://www.osi.ie/publications/geodetic.shtml>)

2001 - New Map Projections for Ireland - Consultation Paper
(see <http://www.osi.ie/publications/papers.shtml>)